



# CIRILLA BOOKMATCH WHITE A

CL-WHA-P-120240-1



SCAN FOR  
PRODUCT FACES

## PRODUCT DETAILS AND SPECIFICATION

### SIZE LIST

Standard Sizes	<b>1200x2400</b>	Surface Finish/es	<b>POLISHED</b>
Sizes on Demand	-	Thickness	<b>9mm</b>

## PRODUCT PERFORMANCE

Glazed Porcelain Tile - Rectified

Technical Features - compliant with standards EN14411 (ISO 13006) Appendice G Group Bla

	TECHNICAL FEATURES	NORMS	REQUIRED STANDARDS	ELINA
Regularity characteristics	Length and width		+/- 0.6% +/- 0.5%	Conforme
	Thickness		+/- 5%	Conforme
	Straightness of sides	ISO 10545-2	+/- 0.5% +/- 0.6%	Conforme / Not applicable to Rustic style irregular edges
	Rectangularity			
	Surface Flatness		cc +/-0.5% e.c +/-0.5% w +/-0.5%	Conforme / Not applicable to "strong" structures
Structural characteristics	Water Absorption	ISO 10545-3	≤0.5%	Conforme
Bulk Mechanical characteristics	Breaking Strength		SPS > 7.5mm S > 1300N	Conforme
	Modulus of rupture	ISO 10545-4	R > 35N/mm <sup>2</sup>	Conforme
Surface Mechanical characteristics	Mohs Hardness	EN 101	≥5 (GL)	Conforme
	Surface abrasion resistance	ISO 10545-7	PEI indicated by manufacturer	Conforme
Thermal and hygrometric characteristics	Thermal shock resistance	ISO 10545-9	Test method available	Conforme
	Resistance to frost	ISO 10545-12	Required	Conforme
Chemical characteristics	Resistance to household chemicals		Class GB min	Conforme
	Resistance to low concentrations of bases and acids	ISO 10545-13	Resistant	Conforme
	Resistance to staining	ISO 10545-14	Class 3 min	Conforme

\*Strictly Recommend the use of 3mm spacer for RECTIFIED TILES  
 \*Strictly Recommend the use of 4mm spacer for NON-RECTIFIED TILES  
 \*Sample is for color reference only. Shade and Caliber may vary during new production.  
 \*For more technical information, please read the overleaf.